



CAMIE-CAMPBELL, INC.
Aerosol and Bulk Industrial Specialty Chemicals



2651 Warrenville Road • Downers Grove, IL 60515
Phone: 800-325-9572 • Fax: 314-968-0741
E-mail: info@camie.com • www.camie.com

CAMIE 563 PRODUCT DATA SHEET

Camie 563 High Strength Fast Tack Adhesive, Low VOC

Is transparent and pressure sensitive. It provides instant tack, is repositionable, has a web-spray pattern and offers the user a low soak in with a high bond strength. Due to this product's low soak-in characteristics and high "green strength", it is especially recommended when bonding polyethylene film to drywall, brick, and concrete block. It is also excellent for use in partitioning and isolating construction areas.

Applications	Use on: wood, polyurethane foam, fabrics, paper, masonry, plastic, polyethylene and painted surfaces. Compatible with most types of styrene board and will not degrade the substrate if sprayed from a distance of 12 to 15 inches.
Container Size	20 Fluid oz. Container
Product Description	High Strength Fast Tack Spray Adhesive
Net Weight	14 Ounces
Cans Per Case	12
Case Dimensions Inches	10 3/4 L x 8 3/16 W x 10 3/16 H
Case Weight	14.7 Pounds
Cases Per Pallet	72 Cases
Appearance	White opaque
Odor	Solvent
Solvent System	Heptane, Acetone and Methyl Acetate
Propellant	Dimethyl Ether, Hydrocarbon 70 PSI
Bond Time	30 Seconds to 2 Minutes
Heat Resistance	120° F
Solids	34%
Spray Pattern	Web
VOC %	38.4%
VOC Compliant for CA & OTC	Yes
Aerosol Flammability Level	Level 3 Aerosols
Warranty Period	One Year From Date of Shipment
Food packaging Adhesive Complies with 21CFR 175.105	No
DOT Proper Shipping Name	Limited Quantity for domestic ground shipment (See SDS for additional shipping information)



CAMIE 563

In as much as CAMIE-CAMPBELL, INC. has no control over the use to which others may put the material, it does not guarantee that the same results described herein will be obtained. Each user should make his own tests to determine the material's suitability for his own particular use.